

線位表


P1	P2	P1	P2
1 白色	1	16 紅色	16
2 紅色	2	17 白色	17
3 地線	3	18 藍色	18
6 黃色	6	19 地線	19
7 橙色	7	23 棕色	23
9 白色	9	24 白色	24
10 綠色	10	22 地線	22
11 地線	11	鐵殼	編織
14 白色	14		
15 紫色	15		

NOTE:

1. 100%OPEN, SHORT & MISWIRE TEST.
2. PAY ATTENTION TO PIN ASSIGNMENTS.

TOLERANCES	REVISIONS				COMPONENT NO :	Arvanics Corporation		
	REV	DESCRIPTION	DATE	APPVD.	DVIP/DVIP-S03BK			
X . + mm					APPROVED :	TITLE :CABLE ASS' Y		
X .X + mm					CHECKED :	REQUIRED DOCUMENTS : *		
X .XX + mm					DRAWN :	SCALE : 1 : 1	SHELLT : 1 / 1	REV : 1
X .XXX + mm					DATE :	DRAWING :		THIRD ANGLE PROJECTION
METRIC (mm)					FILE :			

NO	DESCRIPTION	MATERIAL
1	CABLE	UL 20276 (30#*1P+EAM)*4+30#*5C+AB(AL) 90% ABS 500G 60°C 48H OD:6.0MM CLR-006 BLACK
2	CONN	DVI(18+1) MALE PBT BLACK PIN G/F
3	CASE SHIELD	DVI SHIELD ID:7.5mm PLATED NICKEL
4	SHELL	DVI(18+1) MALE SHELL TIN PLATED
5	PVC	SHORE A 88±2 COLOR:BLACK
6	TUBE	UL/CSA 125°C VW-1 (F4) 300V φ 1.0mm BLACK
7	TUBE	UL/CSA 125°C VW-1 (F4) 300V φ 2.0mm BLACK
8	DUST COVER	CLEAR
9	SCREW	DVI SCREW 2.8*31.5mm#4-40 MOLDED ABS COLOR:BLACK
10	COPPER-FOIL	W8*T0.04mm
11	CORE	F2RH RH 14.2*28.5*7.2mm

TOLERANCES		REVISIONS			COMPONENT NO :	Arvanics Corporation		
		REV	DESCRIPTION	DATE	APPVD.			
X .	+ mm					APPROVED :	TITLE : CABLE ASS' Y	
	- mm					CHECKED :	REQUIRED DOCUMENTS : *	
X .X	+ mm						SCALE : /	SHELLT:2/2
	- mm					DRAWN :	DRAWING :	
X .XX	+ mm					DATE :	FILE :	THIRD ANGLE PROJECTION 
	- mm							
X .XXX	+ mm							
	- mm							
METRIC (mm)								